
PUMA

- Robust blackout fabric with reliable hanging characteristics
- Standard 100 by Oeko-Tex® certified, free from harmful substances
- Greenguard® certification for low-emission products



APPLICATIONS

Not suitable: SG 4905, SG 4900, SG 4907

FABRIC PROPERTIES

Blackout	
25% glass fibre, 75% PVC coated	
407 / 530 g/m²	
0.30 / 0.38 mm	
239 / 295 cm	
244 cm, 300 cm	

FEATURES / TECHNICAL PROPERTIES

6	
Flame retardant	
Applicable in humid areas	
Digital printing	
Oeko-Tex, Greenguard	
Special colours from 1’500 m	
Weldable	

WASHING INSTRUCTIONS

FIRE PROTECTION

Class 1 (CSE RF)
M1 (NF P 92-503/5/7)
Type B (BS 5867-2)

OEKO TEX® STANDARD 100 S08-0170 Hohenstein HTTI

GREENGUARD GOLD

More information
silentgliss.com

Puma

OPTICAL AND SOLAR COEFFICIENTS (± 5%, DIN EN 410)

Colour	R_S	A_S	F_C	g_{tot}
900	56.0	44.0	0.56	0.40
909	22.0	78.0	0.78	0.56
930	5.0	95.0	0.89	0.64
933	45.0	55.0	0.63	0.45
934	60.0	40.0	0.54	0.39

R_S Solar reflectance A_S Solar absorption F_C Shading factor g_{tot} Total g-value

Fc + gtot: Value calculated with glass: 0.72 / Ug = 1.6 W/m² K, DIN EN 13363-1



900 909 930 933 934

Colours shown are not binding

29/03/24